



Motoren Typen	D 80	DS	D 80	DS	D 100	D 100	D300	D 300 S	D 50	H 12	4 DB 85	4 DB 110
Chassis Typen	D 60	D 70	D 80	D 90	D 100	D 200	D300	D 300 S	D 50	H 12	4 DT 45 DT 47	4 DT 70
Bohrung	85	90	85	90	100	100	112	118	112	85	85	110
Hub	104	104	104	104	128	128	140	140	128	104	125	140
Zyl. Inhalt	2.36 lt	2.64 lt	2.36 lt	2.64 lt.	4.02 lt.	4.02 lt.	5.51 lt.	6.12 lt	2.52 lt.	2.36 lt.	2.85 lt.	5.32 lt.
Leistung	30 PS	40 PS	30 PS	40 PS	50 PS	50 PS	60 PS	80 PS	28 PS	28 PS	28 Ps	60 PS
Drehzahl max.	1900	2000	1900	2000	1880	1880	1750	1800	1700	1700	1800	1600
Drehmoment	12 kgm	15.4 kgm	12 kgm	15.4 kgm	20.9 kgm	20.9 kgm	28.4 kgm	35.2 kgm	11.8 kgm	11.8 kgm	11.2 kgm	27 kgm
Düsenart	Flachsitz	4 Loch	Flachsitz	4 Loch	Flachsitz DB 451 LS	Flachsitz DB 451 LS	Flachsitz DB 451 LS	4 Loch	Flachsitz		Pilzdüse	4 Loch
Düsen Nr. Kerzen Nr. H12	DB 452 LS	DA 140 LSD 70	DB 452 LS	DA 140 LSD 70	4 Loch DL 90 S 30 90LSHW ED 322 Z4	4 Loch DL 90 S 30 DA 90LSHWE D 322 Z4	4 Loch DL 90 S 30 DA 90LSHW ED 322 Z4	ED 322 Z4	DB 452 LS	W95 T 1 M14	CBD 876a	CTD 875 a
Düsendruck	180 at	180 at	180 at	180 at	180 at	180 at	180 at	180 at	180 at		180 at	180 at
Einspitzpumpe	PES 4A 60B 120 RS 168	PES 4A 70B 120 RS 168	PES 4A 60B 120 RS 168	PES 4A 70B 120 RS 168	PES 4A 80 B 320/3RS 342 EM 480B 1120	PES 4A 80 B 320/3RS 342 EM 480B 1120	PE 4B 80 D 320 S750	EM 4 85 D 2120Z16	EM 280 1120 Z1 D		PE 4A 60A 420S 338	PE 4B 80 D 320S 490
Regler	EP/ M 60 A 88	ER/ RSV 300 1050A 1/11	EP/ M 60 A 88	ER/ RSV 300 1050A 1/11	ER/ RSV 300 300/950A 1/11	ER/ RSV 300 300/950A 1/11	ERA 1D/8 9650 +300-1020	ERA 1D/8 9650 +300-1020	ERB 3c Z1 230/600/900		Vacumregler	RP 300/850 BD 105/1
Ventilspiel	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.3-0.4	0.2-0.3	0.3-0.4	0.3-0.4
Förderbeginn	33°± 2°	35°± 2°	33°± 2°	35°± 2°	28°± 2°	28°± 2°	28°± 2°	28°± 2°	28°± 2°	32°± 2°	25°± 2°	25°± 2°
Anzugsdrehmoment												
Kurbelwellenlager	18 kgm	18 kgm	18 kgm	18 kgm	18 kgm	18 kgm	19.5 kgm	19.5 kgm	18 kgm	18 kgm	18 kgm	18 kgm
Pleuelstangenkopf	12.5 kgm	12.5 kgm	12.5 kgm	12.5 kgm	12.5 kgm	12.5 kgm	13 kgm	13 kgm	12.5 kgm	12.5 kgm	12.5 kgm	12.5 kgm
Düsenbefestigung	1.5 kgm	1.5 kgm	1.5 kgm	1.5 kgm	1.5 kgm	1.5 kgm	1.5 kgm	1.5 kgm	1.5 kgm		1.5 kgm	1.5 kgm
Zylinderkopf	16.5 kgm	16.5 kgm	16.5 kgm	16.5 kgm	16.5 kgm	16.5 kgm	19.5 kgm	19.5 kgm	16.5 kgm	16.5 kgm	16.5 kgm	16.5 kgm
Schwungrad	14 kgm	14 kgm	14 kgm	14 kgm	16 kgm	16 kgm	16 kgm	16 kgm	14 kgm	14 kgm	16 kgm	16 kgm